



DCX50

HF Drivers - 2 Inches

160 W continuous program power capacity
 2' horn throat diameter
 400 - 16000 Hz response
 108.5 dB sensitivity
 Neodymium magnet assembly
 Time coherent coaxial design

Specification

| | |
|-----------------------|-----------------|
| Throat Diameter | 50 mm (2 in) |
| Nominal Impedance | 8 ohm |
| Minimum Impedance | 8 MF - 7 HF ohm |
| Frequency Range | 0.4 - 16 Hz |
| Recommended Crossover | 0.4 kHz |

MF UNIT

| | |
|------------------------------|--------------|
| Sensitivity (1W/1m) | 108.5 dB |
| Continuous Power Handling | 160 W |
| Nominal Power Handling (AES) | 80 W |
| Voice Coil Diameter | 51 mm (2 in) |
| Winding Material | Aluminium |
| Diaphragm material | Composite |

HF UNIT

| | |
|------------------------------|----------------|
| Sensitivity (1W/1m) | 108.5 dB |
| Nominal Power Handling (AES) | 20 W |
| Continuous Power Handling | 40 W |
| Voice Coil Diameter | 32 mm (1.2 in) |
| Winding Material | Aluminium |
| Diaphragm material | Mylar |

Mounting & Shipping

| | |
|------------------|------------------------------------|
| Overall Diameter | 152 mm (6 in) |
| Depth | 108 mm (4.25 in) |
| Net Weight | 3.3 kg (7.3 lb) |
| Shipping Weight | 3.5 kg (7.7 lb) |
| Shipping Box | 170x170x140 mm (6.7x6.7x5.5 in) |

| | |
|--------------------------|-----------|
| Replacement Diaphragm MF | MMDDCX08 |
| Replacement Diaphragm HF | MMDTWDCX8 |